

DEGREASER GP

- * **FAST ACTING** - Save time and labour.
- * **VERSATILE** - Harmless to most metals and oil resistant paint.
- * **EASY TO USE** - No need for special equipment which requires heating.
- * **ECONOMICAL** - Can be diluted with up to 8 parts of kerosene or mineral spirits.
- * **SAFE** - Non-caustic, non-alkaline, no harmful vapours.

PRODUCT DESCRIPTION

A-515 is a concentrated emulsifying cleaner-degreaser. It contains solvent carrier, emulsifier and surfactants for removal of greases, oil, dirt, carbons and other soil, from machinery parts, engine room, transport depot floor, marine bilges, compressors, radiators, decks, bulkheads, marine vessels, oil tanks and metal surfaces.

A-515 is also recommended for all type of industries and maintenance workshops.

A-515 is also suitable for use as an oil dispersant.

DIRECTIONS FOR USE

MACHINERY & ENGINE CHASSIS :- Used concentrated for heavy contamination or dilute 1 part of **A-515** with 5 - 8 parts of kerosene or diesel. Apply with a low volume sprayer and allow it to work for 10 - 20 minutes, and then flush off with water under pressure.

COLD TANK CLEANING :- Dilute 1 part of **A-515** with 8 parts of kerosene in a metal tank. Soak parts for 30 minutes to 2 hours as required, and then rinse clean with a high pressure water.

WASHING TRUCKS & EQUIPMENTS :- Dilute 1 part of **A-515** with 20 - 30 parts of water. Apply and scrub with cloth or soft brush and then rinse clean.

TANK CLEANING :- Spray or swab the entire surface to be cleaned with neat **A-515**. Allow to soak for 10 to 20 minutes. Pressure flush the entire surface with a hose. Pump the solution into the bilge and allow the tank to air dry.



SPECIFICATION

FLASH POINT : Above 65 °C
COLOUR : Clear Amber
FORM : Liquid
DENSITY : 0.84 – 0.88
STABILITY : Stable under normal condition

CHEMICAL PROPERTIES

Aromatic solvents, emulsifier, wetting and dispersing agents.

SAFETY AND HANDLING INFORMATION

Protective Measures	Use with good industrial hygiene and avoid direct contact. Wear full protective clothing, impervious gloves, goggles or full-face mask. Use in only adequately ventilated areas, equivalent to outdoors. Neat product should not be heated above 55°C.
Spillage & Disposal	Remove all ignition sources and isolate area. Stop leak at source if this is possible. Recover free liquid and ventilate area. Keep petroleum products out of sewers and water courses by impounding. Absorb residue with dry sand or earth. Dispose off absorbed residue as per local authority requirements.
<u>FIRST AID</u>	
Eyes	Rinse eyes with copious amount of water for at least 15 minutes. If irritation persists, seek medical advice.
Skin	Wash skin thoroughly. Remove grossly contaminated clothing, including shoes and launder before reuse. Seek medical attention if necessary.
If Inhaled	Evacuate victim to open air. If breathing or circulation has stopped, apply appropriate resuscitation. Keep at rest. Seek prompt medical attention.
If swallowed	Rinse mouth; then drink 1 or 2 large glasses of water. Do not induce vomiting. Seek prompt medical attention. Never give anything via mouth to an unconscious person.
<u>HANDLING</u>	
Storage & Transportation	Product should be stored and transported in original containers. Keep container lid tightly sealed and dry. Store in a cool and dry area, away from direct sunlight, ignition sources or extreme heat. Keep away from open flames.
Packaging	Supplied in 25 litres and 200 litres non-returnable containers.

To the best of our knowledge, the information contained herein is believed to be accurate and reliable. It is the user's obligation to evaluate and use this product safely and comply with all applicable laws and regulations. Apex Chemicals (S) Pte Ltd and its vendors make no other warranty or representations of any kind or implied, concerning the product including no implied warranty of merchantability. The product is offered solely for your consideration, investigation and verification. No license or immunity under any patents is granted or implied.

