

FILTER CLEANER

DESCRIPTION

A-525 is a synergistic blend of aliphatic and chlorinated aromatic hydrocarbons, and wetting and dispersing agents.

PRODUCT USE

A-525 is a remarkably heavy duty solvent cleaner. It is designed to remove carbonized oils, greases, dirt and other soils from fuel and lubricating oil filters, oil coolers and oil pre-heaters. It may have some effect on certain plastics, it is advisable to test before use.

APPLICATION

A-525 may be applied by spraying, brushing or soaking. **A-525** is mainly used for cleaning permanently fixed oil coolers, oil pre-heaters, metal and ceramic oil filters.

A-525 should be used on a regular maintenance basis. This is to prevent the formation of clogging components which are difficult or impossible to remove.

PHYSICAL DATA

FLASH POINT : Above 65°C PMCC
COLOUR : Clear Amber
DENSITY : 0.85 – 0.90
STABILITY : Infinite under normal conditions

PACKAGING

A-525 is available in 25 litres and 200 litres pails.



SAFETY AND HANDLING INFORMATION

Protective Measures	Use with good industrial hygiene and avoid direct contact. Wear full protective clothing, impervious gloves, goggles or full-face mask. Use in only adequately ventilated areas, equivalent to outdoors.
Spillage & Disposal	Remove all ignition sources and isolate area. Stop leak at source if this is possible. Recover free liquid and ventilate area. Keep petroleum products out of sewers and water courses by impounding. Absorb residue with dry sand or earth. Dispose off absorbed residue as per local authority requirements.
<u>FIRST AID</u> Eyes	Rinse eyes with copious amount of water for at least 15 minutes. If irritation persists, seek medical advice.
Skin	Wash skin thoroughly, remove grossly contaminated clothing, including shoes and launder before reuse. Seek medical attention if necessary.
If Inhaled	Evacuate victim to open air. If breathing or circulation has stopped, apply appropriate resuscitation. Keep at rest. Seek prompt medical attention.
If swallowed	Rinse mouth; then drink 1 or 2 large glasses of water. Do not induce vomiting. Seek prompt medical attention. Never give anything via mouth to an unconscious person.
<u>HANDLING</u> Storage & Transportation	Product should be stored and transported in original containers. Keep container lid tightly sealed and dry. Store in a cool and dry area, away from direct sunlight, ignition sources and extreme heat. Keep away from open flames.
Packaging	Supplied in 25 litres and 200 litres non-returnable containers.

To the best of our knowledge, the information contained herein is believed to be accurate and reliable. It is the user's obligation to evaluate and use this product safely and comply with all applicable laws and regulations. Apex Chemicals (S) Pte Ltd and its vendors make no other warranty or representations of any kind or implied, concerning the product including no implied warranty of merchantability. The product is offered solely for your consideration, investigation and verification. No license or immunity under any patents is granted or implied.

