

# **ELECTRIC MOTOR CLEANER**

## **SOLVENT CLEANER & DEGREASER**

### **DESCRIPTION**

**A-530** is designed for cleaning applications where water is undesirable or hazardous. **A-530** with its powerful and deep penetrating action, cleans away unwanted oils, grease, dirt, wax and carbon particles from all electrical components, metal parts, generators, cables etc.

### **PRODUCT USE**

**A-530** is a slow to medium drying liquid solvent cleaner, specially designed for removing impurities from electric motors and electrical parts, cables etc.

Its key features include:-

- ❑ **NON CHLORO FLUORO CARBON**
- ❑ **CLEANS OILS, GREASE AND DIRT QUICKLY AND EFFECTIVELY**
- ❑ **HIGH FLASH POINT, MEANING SAFER FOR USE**
- ❑ **LOW TOXICITY**
- ❑ **PRODUCE BETTER INSULATION**
- ❑ **ECONOMICAL**

### **DIRECTIONS**

**A-530 can only be used in well-ventilated areas.** Use this cleaner neat, either by spraying, bathing or brushing. When used in a bath, the container should have a lid to prevent evaporation. The duration of immersion depends on the degree of contamination, Hard deposits may have to be removed by brush. The components are then blow off with air-pressure gun or allowed to air dry. **A-530** may affect some types of rubber or plastics from the components. It is highly recommended to test on a small area for any reaction before cleaning.

### **PHYSICAL DATA**

APPEARANCE	: Liquid
COLOUR	: Colourless
BOILING POINT	: NA
SPECIFIC GRAVITY AT 25°C	: 1.30 – 1.45
ODOR	: Characteristic
pH VALUE	: Not Applicable
FLASH POINT	: > 65°C
SOLUBILITY IN WATER	: NA
RELATIVE VAPOR DENSITY (AIR=1)	: NA
STABILITY	: Stable under normal conditions of use



## **SAFETY AND HANDLING INFORMATION**

Protective Measures	Use with good industrial hygiene and avoid direct contact. Wear full protective clothing, impervious gloves, goggles or full face mask. Do not use in enclosed space. Use in only adequately ventilated areas, equivalent to outdoors. If adequate ventilation is not possible, use of breathing apparatus is strongly recommended.
Spillage & Disposal	Remove all ignition sources and isolate area. Stop leak at source if this is possible. Recover free liquid and ventilate area. Keep petroleum products out of sewers and watercourse by impounding. Absorb residue with dry sand or earth. Dispose off absorbed residue as per local authority requirements.
<b><u>FIRST AID</u></b> Eyes	Rinse eyes with copious amount of water for at least 15 minutes. If irritation persists, seek medical advice.
Skin	Wash skin thoroughly. Remove grossly contaminated clothing, including shoes and launder before reuse. Seek medical attention if necessary.
If Inhaled	Evacuate victim to open air. If breathing and/or circulation have stopped, apply appropriate resuscitation. Keep at rest. Seek prompt medical attention.
If swallowed	Rinse mouth; then drink 1 or 2 large glasses of water. Do not induce vomiting. Seek prompt medical attention. Never give anything via mouth to an unconscious person.
<b><u>HANDLING</u></b> Storage & Transportation	Product should be stored and transported in original containers. Keep container lid tightly closed. Store in a cool and dry area, away from direct sunlight, ignition sources and extreme heat. Keep away from open flames. Open container slowly to control possible pressure release.
Packaging	Supplied in 25 litres and 200 litres non-returnable containers.

To the best of our knowledge, the information contained herein is believed to be accurate and reliable. It is the user's obligation to evaluate and use this product safely and comply with all applicable laws and regulations. Apex Chemicals (S) Pte Ltd and its vendors make no other warranty or representations of any kind or implied, concerning the product including no implied warranty of merchantability. The product is offered solely for your consideration, investigation and verification. No license or immunity under any patents is granted or implied.



**® APEX CHEMICALS (S) PTE LTD**

132 TUAS SOUTH AVENUE 2  
WEST POINT BIZHUB, SINGAPORE 637171  
TEL: 64835350 FAX: 64835359  
E-mail: apexchem@singnet.com.sg

