



Quality Chemicals
with
excellent performance

APEX CHEMICALS

DESCRIPTION

APEX SMITH 88 is specially formulated for the removal of soot deposits, medium - heavy oil contaminations.

APEX SMITH 88 can be used for cleaning and removal of animal and vegetable oils from cargo tanks. Suitable for all Annex II cargo.

DIRECTIONS FOR USE

TANK CLEANING

APEX SMITH 88 can be used in re-circulation or direct injection methods.

APEX SMITH 88 is highly concentrated. For manual cleaning, APEX SMITH 88 can be diluted up to 50 parts of water, depending on the degree of contamination.

It is recommended to pre-wash tank with hot water at about 50°C to 60°C before applying APEX SMITH 88. Transfer 2% – 5% concentrated solution of APEX SMITH 88 into the tank to be cleaned. Allow circulation through a pumping system for a period of 2-5 hours.

APEX SMITH 88 is applied to the pre-wash system by spraying the tank surfaces thoroughly. Allow the solution to penetrate and react for about 30 minutes. Then rinse all tank surfaces thoroughly with hot water at about 60°C. The dosage recommendation for spraying method is 5% - 10%.

Tank Material

Safe to use on stainless steel and resistant coatings.

This product should not be used on zinc coating

APEX SMITH 88

- Removal of Soot Stains (Inert Gas residues)
- High cleaning concentrate
- Biodegradable and very low toxicity to marine life
- Effective and economical
- Effective removal of all Annex II cargo

This information is not to be taken as a warranty or representation for which we assume legal responsibility, nor as a permission, inducement, or recommendation to practice any patented invention without a license. The information is offered solely for your consideration, investigation and



APEX CHEMICALS (S) PTE LTD
132 TUAS SOUTH AVENUE 2, SINGAPORE 637171
TEL:+65 64835350 FAX:+65 64835359
E-mail: apexchem@singnet.com.sg