



Quality Chemicals
with
excellent performance

APEX CHEMICALS

APEX-228 SANI CLEAN

- Water based Tank Cleaner for light oil and mineral removal
- Biodegradable
- Excellent odor control and suppression
- Non-flammable

This information is not to be taken as a warranty or representation for which we assume legal responsibility, nor as a permission, inducement, or recommendation to practice any patented invention without a license. The information is offered solely for your consideration, investigation and verification.



IMO APPROVED
TANK CLEANER

DESCRIPTION

APEX-228 Sani Clean is a non-acidic, non-alkaline, neutral complex biodegradable cleaner. *APEX-228 Sani Clean* is designed for effective suppression of heavy and obnoxious odor, and general disinfection of all types of portable toilets, urinals, garbage cans, cargo areas and refuse storage areas.

APEX-228 Sani Clean works as a cleaning, deodorising and disinfecting agent for removal of edible oils from all coated tanks. It is specially developed for situations where cleaning with normal alkaline or solvent based tank cleaning chemicals are not possible.

APPLICATIONS

APEX-228 Sani Clean can be used for the removal of light vegetable oil, animal oil, fats and light mineral oils in aluminium and zinc silicate coated tanks.

Excellent odor control properties to suppress heavy and obnoxious odor from cargo tanks. *APEX-228 Sani Clean* also provides disinfecting properties for cargo tanks carrying food and other commodities.

DIRECTIONS FOR USE

TANK CLEANING

It is recommended to pre-wash the tanks with hot water at 50°C. For drying and semi-drying oils, a pre-wash with cold water should be carried out immediately after discharge of cargo to retard oxidation and hardening of oils residues.

For light deposits, *APEX-228 Sani Clean* can be diluted with 12 parts of water for every part used.

Spray all the cargo tank surfaces with undiluted *APEX-228 Sani Clean* for heavy or stubborn deposits and allow the product to react for at least 30min. Then rinse all tank surfaces with water at a maximum temperature of 60°C for 45minutes.



APEX CHEMICALS (S) PTE LTD
132 Tuas South Avenue 2, Singapore 637171
Tel:+65 6483 5350 Fax:+65 6483 5359
E-mail: apexchem@singnet.com.sg
URL: www.apex-chemicals.com



CERT. NO. QSP0009