



Quality Chemicals
with
excellent performance

APEX CHEMICALS

APEX-303 ECOCLEAN

- New advanced ecological formula
- Water based degreaser
- Non-flammable
- Non-toxic
- No risk of water pollution during disposal operation
- Compatible with oil / water separators
- Promotes a healthy and pleasant smell in the working area
- Very economical dilution rate
- Compatible with all types of tank coatings

This information is not to be taken as a warranty or representation for which we assume legal responsibility, nor as a permission, inducement, or recommendation to practice any patented invention without a license. The information is offered solely for your consideration, investigation and verification.



IMO APPROVED
TANK CLEANER

DESCRIPTION

APEX-303 EcoClean is a micro emulsion water based cleaner. This product is low toxic, biodegradable and safe to use. It is based on natural citrus oil solvent linked with an advanced surfactant formula. The main applications are for cleaning the engine room, deck cleaning, removal of grease, oil, sludge, polymer compounds, carbon deposits, dirt and grime.

APPLICATIONS

Mixed in different concentrations, this product can be used for many purposes.

- General marine cleaning: removal of grease, oil, sludge, carbon deposits, polymer compounds, general dirt and grime, vegetable and animal oils and greases.
- As an engine room cleaner: for cleaning paintwork, as a carbon remover, to soak tanks, for ultrasonic and high pressure cleaning.
- APEX-303 EcoClean can be used to clean the cargo tank of vegetables, fish, animals, mineral oils, petroleum based chemicals, hydrocarbon freeing of cargo tanks and for the cleaning of double bottoms, deep tanks, bilges etc.
- As a general cleaner, APEX-303 EcoClean is used for bulkheads, deck and toilets. The product is safe to use on most types of plastics and vinyl.

DIRECTIONS FOR USE

TANK-CLEANING When using an automatic tank - wash system inject directly into the BWT line or gun-cleaner in a solution of approx. 10 – 15 lt per 1000 lt of water.

When re-circulating from one tank to the next, use a concentration of approx. 3% - 4%. Use the same solution for approx. 4 - 5 tanks, depending on capacity and contamination.

SPOT CLEANING

If necessary the product can be used neat. Spray on the surface to be cleaned and allow soaking for approx. 30 minutes before washing off with plenty of water. Best results are obtained when the solution is heated up until 40°C - 60°C.



APEX CHEMICALS (S) PTE LTD
132 Tuas South Avenue 2, Singapore 637171
Tel:+65 6483 5350 Fax:+65 6483 5359
E-mail: apexchem@singnet.com.sg
URL: www.apex-chemicals.com



CERT. NO. QSP00009