

AWT-13 DISPERSANT

- Reduce scale and sludge deposits
- Keep oil residue into suspend
- Suspended oil residue and solids can be removed easily by bottom blowdown
- Enhance heat transfer efficiency

PRODUCT DESCRIPTION:

AWT-13 DISPERSANT is a specially formulated dispersant used to prevent suspended solids from adhering to internal boiler surfaces and for on-line removal of existing scale of sludge deposits for low-pressure boilers.

AWT-13 DISPERSANT can be used when boiler water had oil contamination or trace of oil, it will keep the oil droplets into suspend and settle down at the bottom and remove by bottom blowdown as temporary solution.

APPLICATION:

Can be added direct to the hotwell or cascade tank.

DOSAGE:

20 ml/ton of water.

PHYSICAL PROPERTIES

Appearance	: Clear to light pink Straw
Relative Density	: 1.01 – 1.11
Form	: Liquid
pH	: 7.0 – 9.0

Packaging : Supplied in 25 litres non-returnable containers

Important information:

Apex chemicals Safety Data Sheets are available. Safety Data Sheets contain health and safety information for proper products handling procedures to protect your employees. Our Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using.

To the best of our knowledge, the information contained herein is believed to be accurate and reliable. It is the user's obligation to evaluate and use this product safely and comply with all applicable laws and regulations. The above-named supplier and its vendor make no other warranty or representations of any kind or implied, concerning the product including no implied warranty of merchantability. The product is offered solely for your consideration, investigation and verification. No license or immunity under any patents is granted or implied